



PROFI™

Universal Cot Fastener



The dynamically crash-tested **PRO F1 Universal Cot Fastener** is the first truly SAE-compliant cross-compatible fastening system. It is designed for use with:



FERNO POWER X1™



Stryker Power-PRO XT



Stryker Performance-PRO XT

With the PRO F1, you can easily exchange cots between the vehicles in your fleet as needed, knowing that they will be safely secured in compliance with crash-test standards.

- **Universal design accommodates** FERNO POWER X1™, Stryker Power-PRO™ XT, and Stryker® Performance-PRO™ XT.
- **Securely fastens compatible cots** during transport for patient and provider safety
- **Linear guide system** facilitates loading and unloading, even on an angle, reducing lateral cot drift
- **Reduced lateral movement** allows for more efficient loading and unloading



One-touch foot-end release frees cot from the PRO F1 with ease.



SAE J3027-compliant for patient and provider safety in the ambulance.



Cross-compatible design allows for use with FERNO and Stryker cot models.



Universal Cot Fastener

Specifications



| | |
|---------------------|---|
| ITEM NUMBERS | Base Model without ICS: 0567065 With ICS and DC cable: 0567066 |
| INTEGRATED CHARGING | Optional |
| LENGTH | 81 in 2047 mm |
| OVERALL WIDTH | 19 in 471 mm |
| HEIGHT | 6 in 151 mm |
| WEIGHT* | 60.8 lb 27.6 kg |
| MATERIAL | Aluminum, Steel, Zytel |

* Fastener is weighed without ICS and mounting hardware

Features & Benefits

- **Cross-compatible design** accommodates: FERNO POWER X1, Stryker Power-PRO XT, and Stryker Performance-PRO XT
- **Designed for longevity** with durable aluminum, steel, and Zytel® construction
- **Low profile and enclosed construction** minimizes trip hazards
- **One-touch foot-end release button** easily releases cot from fastener
- **Easy to remove and power washable** for cleaning and decontamination
- **110° approach angle** when combined with the POWER X1 Ambulance Cot
- **ICS® Integrated Charging System** integration available for use with the FERNO POWER X1 Ambulance Cot (features a remote charging indicator)
- **IP56 rated** for advanced protection against ingress of dust and liquids
- **Compatible with the FERNO Universal Floor Plate**
- **2-Year Warranty** (Ask your FERNO representative about our extended service agreements)

Compliance

The **PRO F1** has been designed to meet international test standards to increase safety for you and your patient.

- SAE J3027
- CAAS-GVS v1.0
- IP56
- KKK-A-1822F
- NFPA 1917
- AMD 004
- IEC 60601-1-2
- ISTA 1A

The PRO F1 is compliant with the above standards when used with:

- POWER X1 combined with the PRO F1 Compatibility Kit
- Stryker Power-PRO XT configured for the Stryker Performance-LOAD or Stryker Power-LOAD***
- Stryker Performance-PRO XT configured for the Stryker Performance-LOAD or Stryker Power-LOAD***

Compatible Systems

| STANDARD | COT | | | COT FASTENER | | | | PATIENT RESTRAINT | | | |
|--|----------------|----------------------------|----------------------|--------------|--------------------------|--------------------------|------------------------------|--------------------|--------------------------|----------------------|-------------------------------|
| | FERNO POWER X1 | Stryker Performance-PRO XT | Stryker Power-PRO XT | FERNO PRO F1 | Stryker Performance-LOAD | FERNO Rail/Antler Series | Stryker Rail/Antler Series** | FERNO X-Restraints | FERNO BioSafe Restraints | Stryker X-Restraints | Stryker Rugged-X Restraints** |
| KKK-A-1822F through change notice 11 (SAE J3027) | • | | | • | | | | • | | | |
| | • | | | • | | | | | • | | |
| | • | • | | • | • | | | • | | • | |
| | | • | • | • | • | | | | | • | • |
| CAAS-GVS v1.0 (2016) (SAE J3027) | • | | | • | | | | • | | | |
| | • | | | • | • | | | • | • | | |
| | | • | | • | | | | | | • | |
| | | • | • | • | • | | | | | • | • |
| NFPA 1917 (2016) (SAE J3027) | • | | | • | | | | • | | | |
| | • | | | • | • | | | • | • | | |
| | • | • | | • | | | | • | | • | |
| | | • | • | • | • | | | | | • | • |
| KKK-A-1822F through change notice 8 (AMD 004) | • | | | | | • | | • | | | |
| | • | | | | | • | | • | | | |
| | • | | | | | | • | • | • | | |
| | • | • | | | | • | • | | • | • | • |

** As advertised

When used in conjunction with the manufacturer supplied floor plate system and safety hook, each of the combinations listed in the matrix complies with the respective standard listed.

***Power-PRO XT, Performance-PRO XT, Performance-LOAD*, and Power-LOAD* are trademarked products of Stryker Corporation. FERNO is not associated with Stryker Corporation. FERNO reserves the right to change specifications without notice.

